

SPECIFICATIONS

imageRUNNER ADVANCE C5000 Series

Type	Desktop		
Maximum Original Size	A3		
Copy Sizes	Cassette	305 x 457mm, A3, A4, A4R, A5R Custom Size 139.7 x 182mm to 304.8 x 457.2mm Optional Envelope Feeder, COM10 No.10, Monarch, DL, ISO-B5, ISO-C5	
	Stack Bypass	A5R - SRA3 (320 x 450mm), Envelopes Custom Size 99 x 140mm to 320 x 457mm	
Resolution	Reading	600dpi x 600dpi	
	Copying	600dpi x 600dpi	
	Printing	1200dpi x 1200dpi (text/line only)	
Copy/Print Speed	A4	C5051: 51ppm (B&W/Color) C5045: 45ppm (B&W/Color) C5035: 35ppm (B&W/Color) C5030: 30ppm (B&W/Color)	
		A3	C5051: 26ppm (B&W/Color) C5045: 26ppm (B&W/Color) C5035: 18ppm (B&W/Color) C5030: 18ppm (B&W/Color)
			Zoom
	Black-and-White		4.0sec (51/45ppm model), 5.5sec (35/30ppm model)
	Full Color	6.5sec (51/45ppm model), 8.9sec (35/30ppm model)	
	Warm-Up Time	38 seconds	
Multiple Copies/Prints	1 to 999 sheets		
Duplexing	Standard automatic stackless		
Paper Weight	Cassette	52 to 209gsm	
	Stack Bypass	52 to 256gsm	
	Duplex	52 to 209gsm	
Paper Capacity	Standard	550 sheets x2 cassettes (80gsm) Stack Bypass: 100 sheets (80gsm)	
	Optional	550 sheets x2 cassettes (80gsm)	
	Paper Deck	2,700 sheets (80gsm)	
	Total capacity	5,000 sheets	
CPU	1.2GHz		
Memory	Standard: 2GB RAM Maximum: 2.5GB RAM		
Hard Disk Drive	Standard	80GB (Available Disk Space: 10GB)	
	Maximum	250GB (Available Disk Space: 115GB)	
Interface	Ethernet	1000Base-T/100Base-TX/10Base-T	
	Wireless LAN	(IEEE802.11b/g, Optional), USB2.0	
Power Supply	220-240V AC, 50/60Hz		
Power Consumption	1.8kW max (51/45ppm), 1.3kW max (35/30ppm)		
Dimensions (WxDxH)	620 x 760 x 982mm (with 1PDS) / 1230mm (with 1PDS & CFU)		
	620 x 735 x 938mm (with DADF) / 1186mm (with DADF & CFU)		
	620 x 735 x 826mm (with Platen cover) / 1074mm (with Platen cover & CFU)		
Weight	Approx. 170kg (with 1PDS)		
	Approx. 153kg (with DADF)		
Print Specification			
PDL	UFR II (Standard), PCL 5c/6 (Optional), Adobe PostScript 3 (Optional)		
Resolution	1200dpi x 1200dpi (Text/Line only), 600dpi x 600dpi		
Memory	2GB (Uses Main Unit RAM)		
Hard Disk	Standard 80GB (Available Disk Space: 10GB) Maximum 250GB (Available Disk Space: 115GB)		
CPU	Canon Custom Processor, 1.2GHz (Uses Main unit CPU)		
PS Fonts	Roman 136		
PCL Fonts	Roman93, Bitmap10, OCR2		
Supported OS	PCL	Windows 2000/XP/Server2003/Vista/Server2008/Win7	
	Adobe PostScript 3	Windows 2000/XP/Server2003/Vista/Server2008/Win7, Mac OS X (10.4.9 or later)	
UFR II	Windows 2000/XP/Server2003/Vista/Server2008/Win7/Linux, Mac OS X (10.4.9 or later)		
Mac-PPD	Mac OS 9.1 or later, Mac OS X (10.2.8 or later)		
Interface	Ethernet	1000Base-T/100Base-TX/10Base-T	
	Wireless LAN	(IEEE802.11b/g, Optional), USB2.0	
Network Protocol	TCP/IP (LPD/Port9100/WSD/IPP/PPS/SMB/FTP), IPv6, IPX/SPX (NDS, Bindery), AppleTalk		
Pull Scan	Network TWIN Driver (75 to 600dpi 24bit color/8bit grayscale/2bit Black & White)		
Optional Accessories			
imagePASS-B1			
PDL	PCL5c/6, Adobe PostScript 3		
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi		
Memory	512MB+512MB (Option)		
Hard Disk	80GB		
CPU	Intel Celeron-M M440 1.86GHz		
PS Fonts	136 Adobe PS Fonts		
PCL Fonts	80 Agfa fonts		
Supported OS	Windows 2000/XP/Server2003/Server2008/Vista/Vista SP1, Mac OS X 10.3.9 or later		
Interface	Ethernet 1000Base-T/100Base-TX/10Base-T, USB		
Network Protocol	TCP/IP (LPD/Port9100/IPP/SMB/FTP), Apple Talk		
ColorPASS-GX300 (Optional for C5051)			
PDL	Adobe PostScript 3		
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi		
Memory	2GB		
Hard Disk	160GB		
CPU	Intel Core2 Duo Xeon E8400 2x3.0Ghz		
PS Fonts	136 Adobe PS Fonts		
PCL Fonts	N/A		
Supported OS	Windows 2000/XP/Server2003/Server2008/Vista/Vista SP1, Mac OS X 10.3.9 or later		
Interface	Ethernet 1000Base-T/100Base-TX/10Base-T, USB, D-sub 15-pin connector		
Network Protocol	TCP/IP (LPD/Port9100/IPP/SMB/FTP), Apple Talk		

Send Specification (Standard)		
Scan Speed (A4, 300dpi)	70ipm (Color/B&W), 100ipm for Duplex scan by optional 1PDS	
Scan Resolution	100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi	
Destinations	E-Mail/Internet FAX (SMTP), PC (SMB, FTP), iWDM, WebDAV	
Address Book	LDAP, Local (Max:1800)	
File Format	TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Optimize PDF for Web	
Universal Send Advanced Feature Set-D1		
File Format	Outline PDF (Trace & Smooth), Searchable PDF/XPS, Reader Extensions PDF, Office Open XML	
Universal Send Security Feature Set-D1		
File Format	Encrypted PDF, Device Signature PDF/XPS	
Optional Image Readers		
Color Image Reader Unit-B1 (2-sided Double pass ADF) / Duplex Color Image Reader Unit-B1 (1PDS)		
Paper Size	A3, A4, A4R, A5, A5R	
Paper Weight	Single sided original	42 to 128gsm
	Double sided original	50 to 128gsm
Max. Number of Originals	100 sheets (80gsm) for 2-sided Double pass ADF 150 sheets (80gsm) for 1PDS	
Document Scanning Speed (max.)	2-sided Double pass ADF Copy	A4 46ipm 600dpi (Color/B&W)
	2-sided Double pass ADF Scan	A4 46ipm 300dpi (Color/B&W)
	1PDS Copy	A4 51/70ipm 600dpi (Color/B&W)
	1PDS Scan	A4 70ipm 300dpi (Color/B&W), 100ipm 300dpi for Duplex scan
Dimensions (W x D x H)	2-sided Double pass ADF	620 x 536 x 137mm
	1PDS	618 x 603 x 180mm
Weight	2-sided Double pass ADF	Approx. 8.7kg
	1PDS	Approx. 26.8kg
Cassette Feeding Unit AD1		
Type	2 Front-loading adjustable drawers	
Paper Size	305 x 457mm, A3, A4, A4R, A5R Custom Size 139.7 x 182 mm to 304.8 x 457.2 mm	
Paper Weight	52 to 209gsm	
Paper Capacity	550 sheets (80gsm) x 2 cassettes	
Dimensions (W x D x H)	620 x 700 x 251mm	
Weight	Approx. 27.5 kg	
Paper Deck Unit B1		
Paper Size	A4	
Paper Weight	52 to 163gsm	
Paper Capacity	2,700 sheets (80gsm)	
Dimensions (W x D x H)	372 x 603 x 473mm	
Weight	Approx. 37 kg	
Inner Finisher A1		
Number of Trays	One stack tray (Optional 2nd Tray)	
Tray Capacity	A4, A5, A5R	A4-A5R: 500 sheets
	A3, A4R	A3, A4R: 500 sheets
Staple Position	Corner, Double	
Staple Capacity	A4: 50 sheets	
	A3: 30 sheets	
Dimensions (W x D x H)	865 x 540 x 234mm	
Weight	Approx. 11.5kg (Approx.13kg with optional tray)	
Staple Finisher C1 / Booklet Finisher C1		
Number of Trays	2 Trays	
Tray Capacity	A4, A5, A5R	1300 on upper tray, 1700 on lower tray
	A3, A4R	650 on upper tray, 650 on lower tray
Staple Position	Corner, Double, Booklet stitch (Booklet Finisher only)	
Staple Capacity	A4	50 sheets (80gsm)
	A3, A4R	30 sheets (80gsm)
Booklet Stitch Specifications (Booklet Finisher only)	Paper Size	305 x 457mm, A3, A4R
	Staple Capacity	1 to 16 sheets (64 pages, 52-81gsm) 1 to 10 sheets (40 pages, 82-105gsm)
Dimensions (W x D x H)	Staple Finisher	677 x 646 x 1097mm
	Booklet Finisher	789 x 646 x 1097mm
Weight	Staple Finisher	Approx. 46kg
	Booklet Finisher	Approx. 75kg
Other Optional Accessories		
Color Image Reader Unit-B2, Printer Cover-C1, IR Pedestal (New), Inner 2way Tray-F1, Inner Finisher Additional Tray-A1, Buffer Pass Unit-G1, External 2 Hole Puncher-B1, Copy Tray-J1, Utility Tray-A1, Envelope Feeder Attachment-D1, Tab Feeding Attachment Kit-B1, Key Switch Unit-A2, Copy Card Reader Attachment-B1, Card Reader-C1, CST-HEATER UNIT32 200V, Reader Heater Unit-G1, Cassette Heater Unit-37, PCL Printer Kit-AE1, PS Printer Kit-AE1, Barcode Printing Kit-D1, Encrypted Printing Software-D1, Direct Print Kit (for PDF)-H1, Direct Print Kit (for XPS)-H1, Universal Send Digital User Signature Kit-C1, Super G3 FAX Board-AE1, Super G3 2nd Line Fax Board-AE1, Super G3 3rd/4th Line Fax Board-AE1, Remote Fax Kit-A1, Expansion Bus-F1, IPsec Board-B2, Wireless LAN Board-B1, Web Access Software-H1, 2.5inch/80GB HDD-C1, 2.5inch/250GB HDD-D1, Removable HDD Kit-AC1, HDD Mirroring Kit-D1, HDD Data Encryption & Mirroring Kit-C1, Secure Watermark-B1, Data Erase Kit-C1, Additional Memory Type B (512MB), USB Device Port-B1, Multimedia Reader/Writer-A1, Serial Interface Kit-K1, Copy Control Interface Kit-A1, Document Scan Lock Kit-A1, ACCESS MANAGEMENT SYSTEM KIT-B1, 512MB OPTION MEMORY, Removable HDD Kit-B1, Remote Operators Software Kit-B1, ADF Access Handle-A1, Voice Guidance Kit-F1, Voice Operation Kit-C1		

This brochure and the specifications of the product have been developed prior to the date of product launch. These specifications are subject to change without notice. Therefore no representations or warranties, either express or implied, are made of the fitness of this product for a particular purpose. In no circumstances shall the information in this brochure be considered part of our terms and conditions of sale. You are advised to check the prevailing specification immediately prior to purchase. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.