

# SPECIFICATIONS imageRUNNER ADVANCE C7000/9000 PRO Series

Type	Console	
Maximum Original Size	A3	
Copy Sizes	Cassette 1.2	A4
	Cassette 3.4	A5R-SRA3 (320 x 450mm), (330 x 483mm)
	Stack Bypass	A5R-SRA3 (320 x 450mm), (330 x 483mm)
		Custom Size, 100 x 148mm to 330.2 x 487.7mm Optional Envelope Feeder, COM10 No.10, Monarch, DL, ISO-B5, ISO-C5
Resolution	Reading	600dpi x 600dpi
	Copying	600dpi x 600dpi
	Printing	1200dpi x 1200dpi (text/line only) 256 Gradations
Copy/Print Speed	A4 (80 gsm)	C9075 PRO: 75ppm (B&W) & 70ppm (Color) C9065 PRO: 65ppm (B&W/Color) C7055: 55ppm (B&W/Color)
	Magnification	Zoom 25-400%
First Copy Time	Black-and-White	C9075 PRO: 4.4sec, C9065 PRO: 4.9sec, C7055: 4.9sec
Warm-Up Time	Full Color	C9075 PRO: 6.0sec, C9065 PRO: 6.6sec, C7055: 6.6sec
		C9075 PRO: 6 minutes C9065 PRO: 5 minutes, C7055: 5 minutes
Multiple Copies/ Prints Duplexing		1 to 9999 sheets
Paper Weight	Cassette	52 to 220gsm
	Stack Bypass	52 to 300gsm
	Duplex	52 to 220gsm
Paper Capacity	Standard	1,100 sheets x2 cassettes (80gsm) 550 sheets x2 cassettes (80gsm) Stack Bypass: 100 sheets (80gsm)
	Paper Deck	3,500 sheets, Multi-drawer Paper deck: 6,000 sheets
	Total Capacity	6,900 sheets, Multi-drawer Paper deck: 9,400 sheets
CPU	Canon Custom Processor, 1.2GHz	
Memory	Standard: 2GB RAM Maximum: 2.5GB RAM	
Hard Disk Drive	Standard 80GB (Available Disk Space: 10GB) Maximum 1TB (Available Disk Space: 675GB)	
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T), Wireless LAN (IEEE802.11b/g, Optional), USB2.0	
Power Supply	220-240V AC, 50/60Hz	
Power Consumption	3KW max. (C9075 PRO & C9065 PRO), 2KW max. (C7055)	
Dimensions (WxDxH)	1180 x 932 x 1403mm (with 1PDS, Upright Control panel, C9075 PRO & C9065 PRO)	
Weight	Approx. 288 kg (with 1PDS & Upright Control Panel)	
	Approx. 282 kg (with 1PDS, C7055)	
<b>Print Specification</b>		
PDL	UFRII (Standard), PCL 5c/6 (Optional), Adobe PostScript 3 (Optional)	
Resolution	1200dpi x 1200dpi (Text/Line only), 600dpi x 600dpi	
Memory	2GB (Uses Main unit RAM)	
Hard Disk	Standard 80GB (Available Disk Space: 10GB) Maximum 1TB (Available Disk Space: 675GB)	
CPU	Canon Custom Processor, 1.2GHz (Uses Main unit CPU)	
PS Fonts	Roman 136	
PCL Fonts	Roman93, Bitmap10, OCR2	
Supported OS	PCL	Windows 2000/XP/Server2003/Vista/Server2008/Win7
	Adobe PostScript 3	Windows 2000/XP/Server2003/Vista/Server2008/Win7, Mac OSX (10.4.9 or later)
UFR II	Windows 2000/XP/Server2003/Vista/Server2008/Win7/Linux, Mac OSX (10.4.9 or later)	
Mac-PPD	Mac OS 9.1 or later, Mac OSX (10.2.8 or later)	
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T), Wireless LAN (IEEE802.11b/g, Optional), USB2.0	
Network Protocol	TCP/IP (LPD/Port9100/WSD/IPP/PPS/SMB/FTP), IPv6, IPX/SPX(NDS, Bindery), AppleTalk	
Pull Scan	Network TWAIN Driver (75 to 600dpi 24bit color/8bit grayscale/2bit Black & White)	
<b>Optional Accessories</b>		
<b>imagePASS-A1</b>		
PDL	PCL5c/6, Adobe PostScript 3	
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi	
Memory	512MB+512MB (Option)	
Hard Disk	80GB	
CPU	Intel Celeron-M M440 1.86GHz	
PS Fonts	136 Adobe PS Fonts	
PCL Fonts	80 Agfa fonts	
Supported OS	Windows 2000/XP/Server2003/Server2008/Vista/Vista SP1, Mac OSX 10.3.9 or later	
Interface	Ethernet 1000Base-T/100Base-TX/10Base-T, USB	
Network Protocol	TCP/IP (LPD/Port9100/IPP/SMB/FTP), AppleTalk	
<b>ColorPASS-GX300</b>		
PDL	Adobe PostScript 3	
Resolution	1200dpi x 1200dpi, 600dpi x 600dpi	
Memory	2GB	
Hard Disk	160GB	
CPU	Intel Core2 Duo Xeon E8400 2x3.0GHz	
PS Fonts	136 Adobe PS Fonts	
PCL Fonts	N/A	
Supported OS	Windows 2000/XP/Server2003/Server2008/Vista/Vista SP1, Mac OSX 10.3.9 or later	
Interface	Ethernet 1000Base-T/100Base-TX/10Base-T, USB, D-sub 15-pin connector	
<b>Send Specification (Standard)</b>		
Scan Speed (A4, 300dpi)	120ipm (Color/B&W), 200ipm (B&W)/140ipm (Color) with optional 1PDS	
Scan Resolution	100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi	
Destinations	E-Mail/Internet FAX (SMTP), PC (SMB, FTP), iWDM, WebDAV	
Address Book	LDAP, Local (Max.1800)	
File Format	TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Optimize PDF for Web	

<b>Universal Send Security</b>		
<b>Feature Set-D1</b>		
File Format	Encrypted PDF, Device Signature PDF/XPS	
<b>Optional Image Readers</b>		
<b>Duplex Color Image Reader Unit-A1 (1PDS)</b>		
Paper Size	A3, A4, A4R, A5, A5R	
Paper Weight	Single Sided Original	38 to 220gsm
	Double Sided Original	50 to 220gsm
Max. Number of Originals	300 sheets (80gsm)	
Document Scanning Speed (max.)	Copy (Single Side)	A4 120ipm 600dpi (B&W), 70ipm 600dpi (Color)
	Scan (Single Side)	A4 120ipm 300dpi (Color/B&W)
	Copy (Double Side)	A4 120ipm 600dpi (B&W), 70ipm 600dpi (Color)
	Scan (Double Side)	A4 200ipm 300dpi (B&W), 140ipm 300dpi (Color)
Dimensions (W x D x H)	635 x 590 x 262mm	
Weight	Approx. 38.9kg	
<b>Paper Deck Unit-A1</b>		
Paper Size	A4	
Paper Weight	52 to 220gsm	
Paper Capacity	3,500 sheets (80gsm)	
Dimensions (W x D x H)	323 x 583 x 570mm	
Weight	Approx. 37kg	
<b>POD Deck Lite-A1</b>		
Paper Size	A3, A4, A4R, SRA3, 330 x 489mm	
Paper Weight	52 to 300gsm	
Paper Capacity	3,500 sheets (80gsm)	
Dimensions (W x D x H)	601 x 621 x 570mm	
Weight	Approx. 50 kg	
<b>Staple Finisher/Booklet Finisher-B1</b>		
Number of Trays	3 trays	
Tray Capacity (Non Collate)	Tray A: A4/ASR 250 sheets, A3/A4R/SRA3/330 x 489mm	125 sheets
	Tray B: A4/ASR 1,300 sheets, A3/A4R/SRA3/330 x 489mm	650 sheets
	Tray C: A4 2,450 sheets, A5R 1,700 sheets, A3/A4R/SRA3/330 x 489mm	650 sheets
Staple Position	Corner, Double, Booklet Stitch (Booklet Finisher only)	
Staple Capacity (64-81g/m <sup>2</sup> )	A4: 50 sheets A3/A4R: 30 sheets	
Booklet Stitch Specifications (Booklet Finisher only)	Paper Size: A3, A4R Staple Capacity: 16 sheets (64 pages, 64-81gsm) Paper Weight: 64 to 105gsm	
Dimensions (W x D x H)	Staple Finisher	748 x 656 x 1121mm
	Booklet Finisher	748 x 656 x 1121mm
Weight	Staple Finisher	Approx. 48kg
	Booklet Finisher	Approx. 70.5kg
<b>Document Insertion/Folding</b>		
<b>Unit G1</b>		
C-Fold	Paper Size	A4R
	Paper Weight	64 to 105gsm
Z-Fold	Paper Size	A3, A4R
	Paper Weight	64 to 105gsm
Output Capacity of C-Fold	40 sheets	
	Document Insertion Unit	
Dimensions (W x D x H)	Size	A3, A4, A4R, SRA3, 330 x 489mm
	Weight	789 x 646 x 1097mm
	Capacity	100 sheets (80gsm)
Weight	Approx. 76kg	
<b>Other Optional Accessories</b>		
Booklet Finisher-A1, Buffer Pass Unit-F1, Card Reader-C1, Color Image Reader Unit-A1, Copy Card Reader Attachment-A1, Copy Tray-P1, Document Insertion Unit-H1, Document Insertion Unit-J1, External 2 Hole Puncher-A1, External 2/3 Hole Puncher-A1, Inner Booklet Trimmer-A1, Multi-drawer Paper Deck-A1, Paper Deck Double Feeding Detection Kit-A1, Paper Folding Unit-G1, Printer Cover-B1, Professional Puncher-C1, Professional Puncher Integration Unit-B1, Puncher Unit-BF1, Puncher Unit-BG1, Staple Finisher-A1, Utility Tray-A1, Paper Deck Heater Unit-A1, Reader Heater Unit-G1, Barcode Printing Kit-D1, Direct Print Kit (for PDF)-H1, Direct Print Kit (for XPS)-H1, Encrypted Printing Software-D1, Expansion Bus-F1, IPsec Board-B2, PCL Printer Kit-AD1, PS Printer Kit-AD1, Remote Fax Kit-A1, Super G3 2nd Line Fax Board-AD1, Super G3 3rd/4th Line Fax Board-AE1, Super G3 FAX Board-AD1, Universal Send Advanced Feature Set-D1, Universal Send Digital User Signature Kit-C1, Web Access Software-H1, Wireless LAN Board-B1, 3.5inch/1TB HDD-B1, 3.5inch/80GB HDD-A1, Access Management System Kit-B1, Additional Memory Type B (512MB), Copy Control Interface Kit-A1, Data Erase Kit-C1, Document Scan Lock Kit-A1, HDD Data Encryption & Mirroring Kit-C1, HDD Mirroring Kit-D1, Key Switch Unit-B1, Multimedia Reader/Writer-A1, Removable HDD Kit-AB1, Secure Watermark-B1, Serial Interface Kit-K1, USB Device Port-A1, 512MB Option Memory, COMPOSE1, V2.0, GA FEATURE SET V.2.2, Graphic Arts Package, Premium Edition V.2.2, GUI KIT-A1, GUI KIT-B1, IMPOSE V2.7 Roman x 1, IMPOSE V2.7 Roman x 3, IMPOSE V2.7 Roman x 7, Removable HDD Kit-B1, SECURE ERASE V1.1, ADF Access Handle-A1, Control Panel Sheet-A1, Remote Operators Software Kit-B1, Upright Control Panel-A1, Voice Guidance Kit-F1, Voice Operation Kit-C1		
This brochure and the specifications of the product have been developed prior to the date of product launch. These specifications are subject to change without notice. Therefore no representations or warranties, either express or implied, are made of the fitness of this product for a particular purpose. In no circumstances shall the information in this brochure be considered part of our terms and conditions of sale. You are advised to check the prevailing specification immediately prior to purchase. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.		