

# SPECIFICATIONS - imageRUNNER 2500 series

Device	imageRUNNER 2520/2525/2530/2535/2545	
Type	Desktop (Reader Combined + Inner Output)	
Imaging System	Laser Dry Electrostatic Transfer System	
Memory	Standard: 256MB Maximum: 512MB	
Network Interface	Ethernet (100Base-TX/10Base-T), USB 2.0	
Warm Up Time	30 seconds maximum after powering ON 1 seconds maximum from the Sleep mode	
First Copy Output Time	imageRUNNER 2520: 6.4 seconds or less imageRUNNER 2530/2525: 5.4 seconds or less imageRUNNER 2545/2535: 3.9 seconds or less	
Multiple Copies	1 to 999 sheets	
Magnification	25% to 400% (1% increment)	
Maximum Original Size	Max. A3/11"x17"	
Duplex	Standard	
Copy/Print Speed	imageRUNNER 2520: 20ppm imageRUNNER 2525: 25ppm imageRUNNER 2530: 30ppm imageRUNNER 2535: 35ppm imageRUNNER 2545: 45ppm	
Resolution	Reading: 600 x 600 dpi Writing: 1200 x 1200 dpi	
Paper Sources (A4, 80gsm)	imageRUNNER 2520: Standard: 250 sheets paper capacity Maximum: 250 + 3 x 550 sheets paper capacity imageRUNNER 2530/2525: Standard: 250 + 550 sheets paper capacity Maximum: 250 + 3 x 550 sheets paper capacity imageRUNNER 2545/2535: Standard: 2 x 550 sheets paper capacity Maximum: 4 x 550 sheets paper capacity	Standard: 100 sheets Stack Bypass  Standard: 100 sheets Stack Bypass
Acceptable Paper Weights	Paper Cassette: 64 to 90gsm Stack Bypass: 64 to 128gsm	
Main Unit Dimensions (W x D x H)	imageRUNNER 2520: 565 mm x 680 mm x 681 mm (with the platen cover) 565 mm x 693 mm x 771 mm (with the feeder) imageRUNNER 2525/2530: 565 mm x 680 mm x 806 mm (with the platen cover) 565 mm x 693 mm x 896 mm (with the feeder) imageRUNNER 2535/2545: 565 mm x 680 mm x 806 mm (with the platen cover) 565 mm x 693 mm x 907 mm (with the feeder)	
Weight	imageRUNNER 2520: Approx. 50.5 kg imageRUNNER 2525/2530: Approx. 67.7 kg imageRUNNER 2535/2545: Approx. 69.5 kg	
Power Source	imageRUNNER 2520/2525/2530: 220 - 240 V AC, 50/60 Hz imageRUNNER 2535/2545: 220 - 240 V AC, 50/60 Hz	
Maximum Power Consumption	imageRUNNER 2520/2525/2530: Approx. 1.542kW imageRUNNER 2535/2545: Approx. 1.827 kW	
Toner Yield (6% Coverage)	imageRUNNER 2520/2525/2530: Approx. 14,600 sheets (A4) imageRUNNER 2535/2545: Approx. 19,400 sheets (A4)	
Drum Yield	imageRUNNER 2520/2525/2530: Approx. 132,000 sheets (A4) imageRUNNER 2535/2545: Approx. 140,000 sheets (A4)	
<b>Print Specification</b>		
PDL	Standard: UFR II LT Optional: PCL 5e/6, PS3	
Network OS	Windows 2000/XP/Server2003/Vista/Server2008/Win7/Linux, Mac OSX (10.4.9 or later)	
<b>Network ScanGear Specification</b>		
Supported OS	Windows 2000/XP/Server 2003/Vista/Server 2008/Win7	
Resolution	BW: Up to 600 x 600 dpi CL: Up to 300 x 300 dpi	
<b>Optional Accessories</b>		
<b>DADF-AA1 (Only for iR2535/2545)</b>		
<b>DADF-AB1 (Only for iR2520/2525/2530)</b>		
Power Source	From Main Unit	
Stacking Method	Face Down	
Feeder Capacity (80gsm)	DADF-AA1: 100 sheets DADF-AB1: 50 sheets	
Acceptable Originals	A4, A4R, A3, A5, A5R, B4, B5, B5R	
Acceptable Paper Weights	DADF-AA1: 1-sided: 42 to 128gsm 2-sided: 50 to 128gsm DADF-AB1: 52 to 128gsm	

Speed	DADF-AA1: Copying: 45ipm (B&W) Sending: 45/34ipm (B&W/Color) DADF-AB1: Copying: 25ipm (B&W) Sending: 25/25ipm (B&W/Color)
Dimensions (W x D x H)	DADF-AA1: 565 x 540 x 137 mm DADF-AB1: 565 x 544 x 126 mm
Weight	DADF-AA1: Approx. 7.9kg DADF-AB1: Approx. 7.0kg
<b>Inner 2Way Tray-G1</b>	
Power Source	Power Supply Unit-U1 (Optional Accessory)
Stacking Method	Face Down
Paper Weight	64 to 128gsm
Capacity (80gsm)	Tray A: A4/B5: 250 sheets Other sizes: 100 sheets Tray B: A4/B5: 100 sheets Other sizes: 50 sheets
Dimensions (W x D x H)	426mm x 413mm x 109mm
Weight	Approx. 0.6kg
<b>Cassette Module-W1 (Only for iR2520)</b>	
Paper Sizes	A4, A4R, A3, A5R, B4, B5, B5R
Paper Capacity (80gsm)	550 sheets
Power Source	From Main Unit
Power Consumption	Approx. 17.4 W Max
Dimensions (W x D x H)	565mm x 680mm x 97mm
Weight	Approx. 12.8kg
<i>Note: Installation of Cassette Spacer-A1 is required.</i>	
<b>Cassette Module-AE1 (for all models)</b>	
Paper Sizes	A4, A4R, A3, A5R, B4, B5, B5R
Paper Capacity (80gsm)	2 x 550 sheets
Power Source	iR2520/2525/2530: Power Supply Unit-U1 (Optional Accessory) iR2535/2545: From Main Unit
Power Consumption	Approx. 13.3 W Max
Dimensions (W x D x H)	565mm x 680mm x 248mm
Weight	Approx. 24kg
<i>Note: For iR2520, installation of Cassette Spacer-A1 is required.</i>	
<b>Super G3 Fax Board-AG1 (for all models)</b>	
Applicable Line	Public Switched Telephone Network (PSTN), 1 line
Compression Method	MH, MR, MMR, JBIG
Transmission Time	ECM-MMR: Approx. 3.2 seconds G3MR method: Approx. 1.3 seconds G3MH method: Approx. 1.3 seconds JBIG: Approx. 2.6 seconds
Transmission Type	Super G3, G3
Sending Original Sizes	A3, A4, A4R, B5*1, B5R*2, A5*2, A5R*1 *1 - Sent as B4 *2 - Sent as A4
Receiving Paper Sizes	A3, B4, A4, A4R, B5, B5R, A5, A5R
Auto Dial Function	Address Book: 300 destinations; one-touch buttons: 200 destinations
Image Memory	Approx. 1,000 pages
<b>Color Send Kit-Y1 (for all models)</b>	
Sending Method	Email, I-Fax, File-Server (FTP, SMB)
File Format	TIFF (B&W), PDF (B&W/Color), PDF (OCR*) (B&W/Color), JPEG (Color), PDF (Compact) (Color), PDF (Compact + OCR*) (Color)  *OCR functions require installation of Color Send Searchable PDF Kit-C1
Color Mode	Color, B&W
<i>Note: Installation of System Upgrade RAM-C1 is required.</i>	
<b>Other Accessories and Supplies</b>	
FL Cassette-AJ, FL Cassette-AL1, FL Cassette-AK1, Envelope Feeder Attachment-D1, Cassette Spacer-A1, Inner Finisher-B1, Inner Finisher Additional Tray-B1, Stamp Ink Cartridge-C1, Stamp Unit-B1, Staple-J1, 2 Way Unit-B1, Document Tray-J1, Card Reader-E1, Card Reader Attachment-D3, USB Application 3-Port Interface Kit-A1, Serial Interface Kit-J2, Control I/F Cable-A1, ADF Access Handle-A1, Power Supply Unit-U1, PCL Printer Kit-AF1, PS Printer Kit-AF1, Barcode Printing Kit-B1, Color Send Searchable PDF Kit-C1, System Upgrade RAM-C1, NPG-51 Black Toner, NPG-50 Black Toner, NPG-50/51 Drum Unit, CST Heater Unit-37, Heater Kit-J1, iR Pedestal Type K	

For more queries and product demonstrations, please speak with one of our Canon representatives today.