

COPIER

Copying process:	4-drum dry electrostatic transfer system with internal transfer belt
Copy speed:	Full colour: 60/70 copies per minute B/W: 65/75 copies per minute
Resolution:	600 dpi
Warm-up time:	Less than 60 seconds
First output speed:	Full colour: Less than 7.5/6.4 seconds B/W: Less than 5.7/4.9 seconds
Memory:	Standard: 2,048 MB + 320 GB HDD (shared with printer function)
Paper input capacity:	Maximum: 7,400 sheets
Paper output capacity:	Maximum: 4,150 sheets
Paper size:	A6 - A3+ (305 x 458 mm)
Paper weight ¹ :	1st, 2nd paper trays: 52.3 - 216 g/m ² 3rd paper tray: 52.3 - 256 g/m ² Bypass tray: 52.3 - 300 g/m ² Duplex tray: 60 - 169 g/m ²
Dimensions (W x D x H):	750 x 850 x 1,230 mm
Weight:	Less than 298 kg
Power source:	220 - 240 V, 50 - 60 Hz
Power consumption:	Maximum: Less than 2.4 kW

PRINTER

CPU:	Intel® Pentium® M 1.4 GHz
Print speed:	Full colour: 60/70 prints per minute
B/W:	65/75 prints per minute
Printer language:	Standard: PCL5c, PCL6, XPS Option: Adobe® PostScript® 3™
Resolution:	600 - 1,200 dpi
Interface:	Standard: USB 2.0, Ethernet 10 base-T/100 base-TX, Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Gigabit Ethernet
Network protocol:	TCP/IP, IPX/SPX, SMB, AppleTalk
Supported environments:	Windows® 2000/XP/Vista/7/Server 2003/Server 2008, Novell® NetWare® 3.12, 3.2, 4.1, 4.11, 5.0, 5.1, 6.0, 6.5, UNIX Sun®Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11iv2/11iv3, SCO OpenServer 5.0.6/5.0.7/6.0, RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise, IBM® AIX v4.3/5L v5.1/v5.2/v5.3, SAP R/3 3.x or later, my SAP ERP 2004 or later, Macintosh 8.6 or later (OS X Classic), Macintosh OS X v10.1 or later (native mode) ²

SCANNER

Scan speed ³ :	Full colour: Maximum 70 (simplex), 115 (duplex) ipm B/W: Maximum 82 (simplex), 125 (duplex) ipm
Resolution:	Maximum: 600 dpi
Original size:	A5 - A3+ (297 x 432 mm)
Output formats:	TIFF, PDF, High compression PDF, JPEG
Bundled drivers:	Network TWAIN
Scan to e-mail:	SMTP, TCP/IP
Scan to folder:	SMB, FTP, NCP protocol (with login security)

SOFTWARE SOLUTIONS

Standard:	App2Me, SmartDeviceMonitor™, Web SmartDeviceMonitor™, Web Image Monitor
-----------	---

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3, additional G3 (option)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	0.7 seconds (A4, SEF)
Memory capacity:	12 MB standard, 44 MB max.
Memory backup:	Yes

OTHER OPTIONS

2,000-sheet A3 large capacity tray (RT4000), 4,000-sheet A4 large capacity tray (RT43), A3 tray unit, 3,000-sheet finisher with 100-sheet stapler (SR5000), 3,000-sheet finisher with 50-sheet stapler (SR4030), 2,000-sheet booklet finisher (SR4040), Ring binder unit (RB5000), Jogger unit, 9-bin mailbox (CS391), 2-source cover interposer (for finisher SR5000), Cover interposer, Several punch kits, Multi-folding unit (FD5000), Copy tray, Tab sheet unit, Fax unit, SAF memory, 2nd Super G3 port, Copy Connect kit, File Format Converter, SD/USB interface, Browser unit, Data Overwrite Security Unit, Copy Data Security Unit, HDD encryption unit, Professional software solutions

¹ With required settings.

² Macintosh OS X v10.2 is not supported.

³ Based on scan resolution 200 dpi, 1 bit / A4 LEF, MMR.

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.
For availability of models, options and software, please consult your local Ricoh supplier.