

COPIER

Copying process:	Dry electrostatic transfer system
Copy speed:	MP C2051: B/W/Full colour: 20 copies per minute MP C2551: B/W/Full colour: 25 copies per minute
Resolution:	600 dpi
Multiple copy:	Up to 999
Warm-up time:	Less than 22 seconds <sup>1</sup>
First output speed:	Full colour: Less than 9.2 seconds B/W: Less than 6.3 seconds
Zoom:	25 - 400% (in 1% steps)
Memory:	Standard: 1.5 GB + 160 GB Hard Disk Drive
Paper input capacity:	Standard: 2 x 250-sheet paper tray(s) 100-sheet bypass tray Maximum: 1,600 sheets
Paper output capacity:	Maximum: 650 sheets
Paper size:	A6 - A3
Paper weight:	Paper tray 1: 60 - 256 g/m <sup>2</sup> Paper tray 2: 60 - 169 g/m <sup>2</sup> Bypass tray: 52 - 256 g/m <sup>2</sup> Duplex tray: 60 - 105 g/m <sup>2</sup>
Dimensions (W x D x H):	587 x 676 x 845 mm (with ARDF)
Weight:	Less than 100 kg (with ARDF)
Power source:	220 - 240 V, 50 - 60 Hz
Power consumption:	Operation: Maximum 1,680 kW Auto Off mode: 1, 1 W

PRINTER

Print speed:	MP C2051: B/W/Full colour: 20 copies per minute MP C2551: B/W/Full colour: 25 copies per minute
Printer language:	Standard: PCL5c, PCL6 (XL) Option: Adobe® PostScript® 3™, IPDS
Resolution:	1,200 dpi
Interface:	Standard: USB2.0 Host I/F Ethernet 10Base-T/100Base-TX Option: IEEE 1284/ECP Wireless LAN (IEEE 802.11a, b, g, WPA support) USB2.0/SD Slot Ethernet 1000Base-T
Network protocol:	TCP/IP (IP v4, IP v6), IPX/SPX
Supported environments:	Windows® 2000/XP/Vista/7/Server 2003/Server 2008/Server 2008R2, Novell® Netware® 3.12/3.2/4.1/4.11/5.0/5.1/6/6.5/6.5 or later, Sun® Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11iv2, SCO OpenServer 5.0.6/5.0.7/6.0, RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise, IBM® AIX v4.3/5L v5.1/5L v5.2/5L v5.3, Macintosh OS X v10.2 or later, SAP® R/3® 3.x or later, mySAP ERP2004 or later, NDPS Gateway, IBM iSeries, AS/400® using OS/400 Host Print Transform

SCANNER

Scan speed:	B/W: 44 images per minute (A4/LET LEF) Full colour: 44 images per minute (A4/LET LEF)
Resolution:	Maximum 600 dpi
Original size:	A5 - A3
Output formats:	PDF/JPEG/TIFF/High compression PDF
Bundled drivers:	Network, TWAIN
Scan to e-mail:	SMTP, POP3
Scan to e-mail destination addresses:	Maximum 500 per job
Stored destination addresses:	Maximum 2,000
Address book:	Via LDAP or locally on Hard Disk Drive
Scan to folder:	SMB, FTP, NCP
Destination:	Maximum 50 folders per job

SOFTWARE SOLUTIONS

SmartDeviceMonitor™  
Web SmartDeviceMonitor™  
Web Image Monitor

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Modem speed:	Maximum 33.6 Kbps
Resolution:	Standard/detail: 200 x 100 - 200 dpi Maximum: 400 x 400 dpi (option)
Compression method:	MH, MR, MMR, JBIG
Scanning speed:	36 sheets per minute
Memory capacity:	Standard: 4 MB Maximum: 28 MB
Memory backup:	Yes

OTHER OPTIONS

Cabinet, Caster table, 500-sheet paper tray, 2 x 500-sheet paper trays, Internal 500-sheet finisher, Punch unit, Fax unit, Fax stamp ink, Shift tray, Inner one bin tray, Side tray, Envelope feeder, Browser unit, File Format Converter, Data Overwrite Security Unit, Key counter bracket, Remote communication gate BN1, Counter interface unit type A, Card authentication package, PictBridge, USB2.0/SD slot, Unicode font package for SAP, SAF memory, Card reader bracket, GlobalScan NX, Professional software solutions

<sup>1</sup> Warm-up time and power consumption may differ depending on the conditions and environment of the machine  
Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.  
For availability of models, options and software, please consult your local Ricoh supplier.

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.  
For availability of models, options and software, please consult your local Ricoh supplier.